PRODUCT SPECIFICTIONS

BASIC Blower Truck Mesh



PURPOSE & DESCRIPTION

Filtrexx BASIC Blower Truck mesh is compost sock mesh for field installation with blower trucks or track machines. Meet all specs with this versatile, light duty mesh that is good for most applications.

APPLICATIONS

• On-site blower truck installation for sediment control applications such as Perimeter Control and Slope Interruption

FOR ADDITIONAL INFORMATION

Refer to the **Filtrexx Catalog** for full item listings.

Refer to Filtrexx Design Specifications for complete application, design, installation, maintenance, and removal documentation at www.filtrexx.com/specs

FIELD APPLICATION PHOTO REFERENCES



BASIC Blower Truck Mesh field installation.

BASIC Blower Truck Mesh Specifications

DASIC DIONEL Track mesh specifications	
Product Name	BASIC Blower Truck Mesh
Mesh Material Type	5mil High Density Polyethylene (HDPE) Photodegradable
Uses	On-site blower truck installation
Mesh Opening Size	3/8"
Diameters	8", 12", 18"
Functional Longevity/ Project Duration ¹	up to 4 yr
Tensile Strength (ASTM D4595) ²	MD: 211 lbs TD: 79 lbs
Packaging	Rucks
Mesh Color	yellow/black (8") orange/black (12") red/black (18")
Mesh Sample	

¹Functional longevity ranges are estimates only. Site specific environmental conditions may result in significantly shorter or longer time periods. ²Tensile Strength is based on 12" diameter using ATSM D4595. See Filtrexx TechLink #3342 for full tensile strength testing.

Filtrexx Mesh is in compliance with most state & federal agencies including:













Filtrexx® and the branch & leaf logo® are Registered Trademarks used by Filtrexx International.

The information contained herein may be subject to confidential intellectual property of Filtrexx International, including but not limited to US Patents 7,226,240; 7,452,165; 7,654,292; 8,272,812; 8,439,607; 8,740,503; 8,821,076; 9,044,795; 9,945,090; and 9,982,409 or Patents Pending and is the property of Filtrexx International.

Copyright 2005-2021, Filtrexx International, all rights reserved. Unauthorized reproduction prohibited. All statements, product characteristics, and performance data contained herein are believed to be reliable based on observation and testing, but no representations, guarantees, or warranties of any kind are made as to accuracy, suitability for particular applications, or the results to be obtained. Nothing contained herein is to be considered to be permission or a recommendation to use any proprietary process or technology without permission of the owner. No warranty of any kind, expressed or implied, is made or intended.