PRODUCT SPECIFICTIONS

BASIC PLUS+ Blower Truck Mesh



PURPOSE & DESCRIPTION

Filtrexx BASIC PLUS+ Blower Truck mesh is compost sock mesh for field installation with blower trucks or track machines. Meets or exceeds specs with higher durability. Available in larger diameter sizes for any project.

APPLICATIONS

• On-site blower truck installation for sediment control applications such as Perimeter Control and Slope Interruption

FOR ADDITIONAL INFORMATION

Refer to the **Filtrexx Catalog** for full item listings.

Refer to Filtrexx Design Specifications for complete application, design, installation, maintenance, and removal documentation at www.filtrexx.com/specs

FIELD APPLICATION PHOTO REFERENCES



BASIC PLUS+ Blower Truck Mesh field installation.

BASIC PLUS+ Blower Truck Mesh Specifications

Product Name	BASIC PLUS+ Blower Truck Mesh
Mesh Material Type	Multi-Filament Polypropylene (MFPP) Photodegradable
Uses	On-site blower truck installation
Mesh Opening Size	3/8"
Diameters	8", 12", 18", 24", 32"
Functional Longevity/ Project Duration ¹	up to 4 yr
Tensile Strength (ASTM D4595) ²	MD: 236 lbs TD: 223 lbs
Packaging	Rucks
Mesh Color	black
Mesh Sample	

¹Functional longevity ranges are estimates only. Site specific environmental conditions may result in significantly shorter or longer time periods. ²Tensile Strength is based on 12" diameter using ATSM D4595. See Filtrexx TechLink #3342 for full tensile strength testing.

Filtrexx Mesh is in compliance with most state & federal agencies including:













Filtrexx® and the branch & leaf logo® are Registered Trademarks used by Filtrexx International.

The information contained herein may be subject to confidential intellectual property of Filtrexx International, including but not limited to US Patents 7,226,240; 7,452,165; 7,654,292; 8,272,812; 8,439,607; 8,740,503; 8,821,076; 9,044,795; 9,945,090; and 9,982,409 or Patents Pending and is the property of Filtrexx International.

Copyright 2005-2021, Filtrexx International, all rights reserved. Unauthorized reproduction prohibited. All statements, product characteristics, and performance data contained herein are believed to be reliable based on observation and testing, but no representations, guarantees, or warranties of any kind are made as to accuracy, suitability for particular applications, or the results to be obtained. Nothing contained herein is to be considered to be permission or a recommendation to use any proprietary process or technology without permission of the owner. No warranty of any kind, expressed or implied, is made or intended.